

S50i

VoIP PBX

Yeastar S50i je dizajniran da obezbedi robusno rešenje za komunikaciju za mala i srednja preduzeća. Isporučuje se sa kompletnim funkcijama telefonskog sistema kao i sa povećanjem UC kapaciteta sa Linkus UC klijentima. Lako upravljanje, obilje funkcija i brzo automatsko podešavanje (provisioning) omogućavaju da S50i pruži praktično iskustvo pozivanja, bezbednu komunikaciju i omogući korisnicima da zadovolje svoje specifične potrebe u različitim scenarijima.

Karakteristike

Korisnika	50
Najviše istovremenih poziva	20
VoIP linija	50
LAN / WAN	2 10/100 Mbps
Protokol	SIP (RFC3261), IAX2
Protokol prenosa	UDP, TCP, TLS, SRTP
Kodek	G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC, H263, H263P, H264, MPEG4
DTMF	In-band, RFC4733, RFC2833, SIP INFO
IP Servisi	Static IP, DHCP, VPN, Firewall, VLAN, DDNS, PPPoE, QoS, Static NAT, STUN
Automatska sekretarica	5000 min (proširivo)
Kompanijski imenik	500
App Centar	Linkus, Auto podešavanje, LDAP Server, Konferenc. Panel, VPN Server, Billing App*, Hotel App*, char utile h+ Integracija, Zoho Integracija
Spoljašnje skladištenje	SD kartica
Napajanje	AC 100-240V 50/60HZ 0.6A maks
Dimenzije (Š x V x D)	34 cm x 21 cm x 4.4 cm
Težina	1.48 kg
Okruženje	Temperatura rada: 0°C do 40°C, 32°F do 104°F; Temp. skladištenja: -20°C do 65°C, -4°F do 149°F; Vlažnost: 10-90% ne-kondenzujuće
Montaža	1U Rek-montažno

* Funkcije koje imaju oznaku * se dodatno kupuju.

* Moduli za telefoniju (FXS, FXO, ISDN BRI/PRI, GSM/3G/4G) nisu podržani na S50i.



Funkcije

- Linkus UC Clients
- Linkus Cloud Service*
- Remote Management
- Mobility Extension
- Automated Attendant (IVR)
- AutoCLIP
- Attended Transfer
- SLA
- Voicemail
- Ring Group
- Blind Transfer
- Real-time Status Monitor
- Paging/Intercom
- One Touch Recording
- Queue
- Speed Dial
- Music on Hold
- User Permission
- Event Center
- Call Detail Records (CDR)
- Call Forwarding
- Call Monitor
- Call Parking
- Call Pickup
- Call Recording
- Call Routing
- Call Back
- Call Waiting
- Caller ID
- Contacts
- Do Not Disturb (DND)
- Custom Prompt
- Blocklist/Allowlist
- PIN List
- Phone Provisioning
- SIP Forking
- Time Condition
- Dial by Name
- Email to SMS/SMS to Email
- Fax to Email
- T.38 Fax
- User Portal
- DISA
- Distinctive Ringtone
- DNIS
- Firewall
- Hot Standby
- LDAP
- Multi-language System Prompt
- Multi-language System Language
- Multi-site Interconnect